

Topcon's DT-200 Series represents the highest accuracy and value in Digital Theodolite technology. Only Topcon, with 75+ years of experience manufacturing the World's most precise Optical Survey instruments can offer the precision, durability, and advanced technology found in each DT-200.

Make your next job a snap

With Topcon's DT-200 you'll be up and working fast, thanks to its simple interface and large, easy-to-see backlit LCD. There's an optical plummet that makes set up over a control point easy, and a tilt sensor that provides ± 3 minute angle correction. The DT-200 Series features two magnification choices - 26x and 30x, a super-short 3' minimum focus distance for those tight areas, and angle accuracies of 5, 7, and 9 arc seconds.

L = Laser

Add a whole new dimension of accuracy and confidence to your alignment jobs with Topcon's unique DT-200L Series, featuring a 633nm Class II laser beam. It can be used anywhere on your site and seen clearly in direct sunlight up to 165'. Now you can easily and accurately place anchor bolts at regular intervals on a line, set an angle and use the beam to verify your tape measure is properly aligned for the next stake, or "sight in" footers, frames, and tilt-up walls, all without pulling a string!

No matter which DT-200 you choose, you'll experience the simplicity and value that only Topcon can provide.

Topcon. It's time.



DT-200/DT-200L Series
Digital Theodolite



Durability, accuracy, and value, that's Topcon and that's the DT-200 and DT-200L Series of digital theodolites.



Water and dustproof

Get the work done, even in less than perfect conditions. All DT-200/DT-200L Series instruments are rated to IP66, standing up to even the rainiest conditions. And each telescope is gas charged to further avoid moisture intrusion and limit or eliminate lens fogging.



Laser accurate (DT-200L Series only)

Topcon's World Leading laser technology is incorporated in to the DT-200L Series to aid in fast, confident alignment. The 633nm beam is emitted directly from the aperture, but does not impede viewing, in fact it's not even visible when sighting through the lens. (Class II laser beam)



Simple Operation

Each DT-200 provides large, high-contrast, back-lit LCD's on both sides of the instrument. And the five button interface panel is so simple to use your crew won't require any special training to put your DT-200 to use day-in and day-out. (DT-209/209L: single side display)



Fast, reliable data gathering (DT-205/205L)

Eliminate the notebook, pen, and hassle of pages of note taking. Easily connect the DT-200/DT-200L Series to a Field Controller or a laptop computer for continuous download of angle measurements as they are made.

The ultimate in continuous operation

The DT-200/DT-200L Series provides up to 140+ hours of operation in Angle Measurement mode on 4AA batteries, better than any other model! And when it is time to change batteries, it's as easy as snapping out the old ones and snapping in the new.

Even when using the laser, power consumption is extremely low providing 80 hours of continuous operation.



Compact, lightweight, sets-up in seconds. Topcon's DT-200/DT-200L Series Theodolites, all the theodolite you'll ever need.



Accessories (model dependent)

Diagonal Eyepiece (55331)

Roof Plummet (55303)

Solar Eyepiece (55305)

Trough Compass (55323)

Eyepiece Prism w/Darkener (55301)

The Leader in Positioning Technology...

Your local authorized Topcon dealer has the answer for all of your precise positioning needs. Whether you're looking for the World's most advanced and accurate optical survey instruments, GPS+ control for surveying and engineering applications, site layout or grade management on a construction job site, your local Topcon dealer offers the widest range of products to get the job done quickly and accurately.

There's only one company that offers you all of the positioning tools to keep you competitive in today's market. They're only available from Topcon and your local Topcon dealer.

The Leader in Customer Satisfaction...

To ensure that your Topcon product maintains peak performance, your local Topcon dealer offers factory trained and certified service technicians. And just in case service assistance isn't available in your area, our factory offers a repair and support policy second to none.

DT-200/DT-200L Series packages include

- Instrument
- Plumb Bob
- Tool kit
- Waterproof protective cover
- Lint free lens cloth
- Hard shell carry case



Specifications

		DT-205	DT-207	DT-209	DT-205L	DT-207L	DT-209L
Angle Measurement	Accuracy	5"	7"	9"	5"	7"	9"
	Method	Absolute reading	Absolute reading	Absolute reading	Absolute reading	Absolute reading	Absolute reading
	Detecting	Horiz.: 2 sides	Horiz.: 2 sides	Horiz.: 1 side	Horiz.: 2 sides	Horiz.: 2 sides	Horiz.: 1 side
		Vert.: 1 side	Vert.: 1 side	Vert.: 1 side	Vert.: 1 side	Vert.: 1 side	Vert.: 1 side
	Min. reading	1"/5"	5"/10"	10"/20"	1"/5"	5"/10"	10"/20"
Diameter circle	0.5mgon/1mgon	1mgon/2mgon	2mgon/5mgon	0.5mgon/1mgon	1mgon/2mgon	2mgon/5mgon	
Telescope	Magnification	30x	30x	26x	30x	30x	26x
	Length	149mm (5.8")	149mm (5.8")	149mm (5.8")	152mm (5.9")	152mm (5.9")	152mm (5.9")
	Objective Lens	45mm (1.7")	45mm (1.7")	40mm (1.5")	45mm (1.7")	45mm (1.7")	40mm (1.5")
	Field of view	1°30'	1°30'	1°30'	1°30'	1°30'	1°30'
	Resolving power	2.5"	2.5"	2.5"	2.5"	2.5"	2.5"
	Minimum focus	0.9m (2.9')	0.9m (2.9')	0.9m (2.9')	1m (3.2')	1m (3.2')	1m (3.2')
	Stadia ratio	100	100	100	100	100	100
	Stadia constant	0	0	0	0	0	0
	Sighting collimator	Double	Double	Double	Double	Double	Double
Laser Pointer	Method	N/A	N/A	N/A	Focusing	Focusing	Focusing
	Wave length/Power	N/A	N/A	N/A	633nm/0.6mW	633nm/0.6mW	633nm/0.6mW
	Laser class	N/A	N/A	N/A	Class II	Class II	Class II
Display	Unit	2 sides	2 sides	1 side	2 sides	2 sides	1 side
		LCD 7segments	LCD 7segments	LCD 7segments	LCD 7segments	LCD 7segments	LCD 7segments
Data output	Serial signal conn.	RS-232C	N/A	N/A	RS-232C	N/A	N/A
Illumination	Display	Yes	Yes	Yes	Yes	Yes	Yes
	Reticle	Yes	Yes	N/A	Yes	Yes	N/A
Compensator	Tilt sensor	Vertical	N/A	N/A	Vertical	N/A	N/A
	Compensating range	±3'	N/A	N/A	±3'	N/A	N/A
Optical Plummet	Magnification	3x	3x	3x	3x	3x	3x
	Field of view	3°	3°	3°	3°	3°	3°
	Focusing	0.5m ~ ∞	0.5m ~ ∞	0.5m ~ ∞	0.5m ~ ∞	0.5m ~ ∞	0.5m ~ ∞
Level Sensitivity	Plate level	40"/2mm	40"/2mm	60"/2mm	40"/2mm	40"/2mm	60"/2mm
	Circular level	10'/2mm	10'/2mm	10'/2mm	10'/2mm	10'/2mm	10'/2mm
Water protection	Standard	IP66	IP66	IP66	IP66	IP66	IP66
Power supply	Battery	4AA batteries	4AA batteries	4AA batteries	4AA batteries	4AA batteries	4AA batteries
Operating time	Theodolite only	140h	150h	170h	140h	150h	170h
	Laser only	N/A	N/A	N/A	80h	80h	80h
	Theodo. & laser	N/A	N/A	N/A	45h	45h	45h
Operating temp.		-68°F ~ +122°F	-68°F ~ +122°F	-68°F ~ +122°F	-68°F ~ +122°F	-68°F ~ +122°F	-68°F ~ +122°F
		(-20°C ~ +50°C)	(-20°C ~ +50°C)	(-20°C ~ +50°C)	(-20°C ~ +50°C)	(-20°C ~ +50°C)	(-20°C ~ +50°C)
Weight		9lbs (4.1kg)	9lbs (4.1kg)	7.5lbs (3.4kg)	9.25lbs (4.2kg)	9.25lbs (4.2kg)	8lbs (3.6kg)



MARGA SETIA

PUSAT ALAT SURVEY INDONESIA

Jl.H. Kelik No.20 Kelapa Dua Kebon Jeruk Jakarta Barat 11550

Phone: (021) 08128222998, 087770760007

email : info@margasetia.com

Website: www.margasetia.com

TRIMBLE AUTHORIZED DISTRIBUTION PARTNER